

上海邦泉泵业制造有限公司管道泵参数表

从 25-110 至 50-100 (I) A, 流量: 2.5m³/h—29m³/h

型 号	流量		扬程 (m)	效率 (%)	转速 (r/min)	电机功率 (kw)	汽蚀余量 (NPSH)r	重量 (kg)
	m ³ /h	L/s						
25-110	2.8	0.78	16	34	2900	0.55	2.3	26
	4	1.11	15	42				
	5.2	1.44	13.5	41				
25-125	2.8	0.78	20.6	28	2900	0.75	2.3	28
	4	1.11	20	36				
	5.2	1.44	18	35				
25-125A	2.5	0.69	17	35	2900	0.55	2.3	27
	3.6	1.0	16					
	4.6	1.28	14.4					
25-160	2.8	0.78	33	24	2900	1.5	2.3	39
	4	1.11	32	32				
	5.2	1.44	30	33				
25-160A	2.6	0.12	29	31	2900	1.1	2.3	34
	3.7	1.03	28					
	4.9	1.36	26					
32-100	4.5	12.5	12.5	44	2900	0.55	2.0	27
32-100(I)	4.4	1.22	13.2	48	2900	0.75	2.0	32
	6.3	1.75	12.5	54				
	8.3	2.32	11.3	53				
32-125	3.5	0.97	22	40	2900	0.75	2.3	28
	5	1.39	20	44				
	6.5	1.8	18	42				
32-125A	3.1	0.86	17.6	43	2900	0.55	2.3	28
	4.5	1.25	16					
	5.8	1.61	14.4					
32-160	6.5	5	32	44	2900	1.5	2.3	39
32-160A	4	1.1	25	34	2900	1.1	2.0	38
32-160(I)	4.4	1.22	33.2	34	2900	2.2	2.0	4.7
	6.3	1.75	32	40				
	8.3	2.32	30.2	42				
32-200	4.5	12.5	50	32	2900	3	2.0	55
32-200(I)	4.4	1.22	50.5	26	2900	4	2.0	43
	6.3	1.75	50	33				
	8.3	2.32	48	35				
32-200A	2.8	0.78	44.6	34	2900	2.2	2.0	74

	4 5.2	1.11 1.44	44 42.7	40 42				
40-100	4.4 6.3 8.3	1.22 1.75 2.31	13.2 12.5 11.3	48 54 53	2900	0.55	2.3	32
40-100A	3.9 5.6 7.4	1.08 1.56 2.06	10.6 10 9	52	2900	0.37	2.3	32
40-125	4.4 6.3 8.3	1.22 1.75 2.31	21 20 18	41 46 43	2900	1.1	2.3	34
40-125A	3.9 5.6 7.4	1.08 1.56 2.06	17.6 16 14.4	40 45 41	2900	0.75	2.3	33
40-160	4.4 6.3 8.3	1.22 1.75 2.31	33 32 30	35 40 40	2900	2.2	2.3	47
40-160A	4.1 5.9 7.8	1.14 1.64 2.17	29 28 26.3	34 39 39	2900	1.5	2.3	43
40-160B	3.8 5.5 7.2	1.06 1.53 2.0	25.5 24 22.5	34 38 37	2900	1.1	2.3	38
40-200	4.4 6.3 8.3	1.22 1.75 2.31	51 50 48	26 33 32	2900	4.0	2.3	74
40-200A	4.1 5.9 7.8	1.14 1.64 2.17	45 44 42	26 31 30	2900	3.0	2.3	62
40-200B	3.7 5.3 7.0	1.03 1.47 1.94	38 36 34.5	29	2900	2.2	2.3	52
40-250	4.4 6.3 8.3	1.22 1.75 2.31	82 80 74	24 28 28	2900	7.5	2.3	105
40-250A	4.1 5.9 7.8	1.14 1.64 2.17	72 70 65	24 28 27	2900	5.5	2.3	98
40-250B	3.8 5.5 7.0	1.06 1.53 1.94	61.5 60 56	23 27 26	2900	4.0	2.3	77
40-100(I)	8.8	2.44	13.2	55	2900	1.1	2.3	34

	12.5 16.3	3.47 4.53	12.5 11.3	62 60					
40-100(I)A	8 11 14.5	2.22 3.05 4.03	10.6 10 9		60	2900	0.75	2.3	32
40-125(I)	8.8 12.5 16.3	2.44 3.47 4.53	21.2 20 17.8	49 58 57		2900	1.5	2.3	38
40-125(I)A	8 11 14.5	2.22 3.05 4.03	17 16 14		57	2900	1.1	2.3	33
40-160(I)	8.8 12.5 16.3	2.44 3.47 4.53	33 32 30	45 52 51		2900	3.0	2.3	56
40-160(I)A	8.2 11.7 15.2	2.28 3.25 4.22	29 28 26	44 51 50		2900	2.2	2.3	47
40-160(I)B	7.3 10.4 13.5	2.38 2.89 3.75	23 22 20.5		50	2900	1.5	2.3	43
40-200(I)	8.8 12.5 16.3	2.44 3.47 4.53	51.2 50 48	38 46 46		2900	5.5	2.3	85
40-200(I)A	8.3 11.7 15.3	2.31 3.25 4.25	45.0 44 42	37 45 45		2900	4.0	2.3	75
40-200(I)B	7.5 10.6 13.8	2.08 2.94 3.83	37 36 34		44	2900	3	2.3	63
40-250(I)	8.8 12.5 16.3	2.44 3.47 4.53	81.2 80 77.5	31 38 40		2900	11	2.3	145
40-250(I)A	8.2 11.6 15.2	2.28 3.22 4.22	71.0 70 68		38	2900	7.5	2.3	95
40-250(I)B	7.6 10.8 14	2.11 3.0 3.89	61.4 60 58		37	2900	5.5	2.3	94
40-250(I)C	7.1 10.0 13.1	1.97 2.78 3.64	53.2 52 50.4		36	2900	5.5	2.3	88
50-100	8.8	2.44	13.6	55		2900	1.1	2.3	36

	12.5 16.3	3.47 4.53	12.5 11.3	62 60				
50-100A	8 11 14.5	2.22 3.05 4.03	11 10 9	60	2900	0.75	2.3	35
50-125	8.8 12.5 16.3	2.44 3.47 4.53	21.5 20 17.8	49 58 57	2900	1.5	2.3	43
50-125A	8 11 14.5	2.22 3.05 4.03	17 16 14	57	2900	1.1	2.3	38
50-160	8.8 12.5 16.3	2.44 3.47 4.53	33 32 30	45 52 30	2900	3.0	2.3	59
50-160A	8.2 11.7 15.2	2.28 3.25 4.22	29 28 26	44 51 50	2900	2.2	2.3	51
50-160B	7.3 10.4 13.5	2.38 2.89 3.75	23 22 20.5	50	2900	1.5	2.3	47
50-200	8.8 12.5 16.3	2.44 3.47 4.53	52 50 48	38 46 46	2900	5.5	2.3	101
50-200A	8.3 11.7 15.3	2.31 3.25 4.25	45.8 44 42	37 45 45	2900	4.0	2.3	80
50-200B	7.5 10.6 13.8	2.08 2.94 3.83	37 36 34	44	2900	3	2.3	68
50-250	8.8 12.5 16.3	2.44 3.47 4.53	82 80 77.5	29 38 40	2900	11	2.3	160
50-250A	8.2 11.6 15.2	2.28 3.22 4.22	71.5 70 68	38	2900	7.5	2.3	115
50-250B	7.6 10.8 14	2.11 3.0 3.89	61.4 60 58	37	2900	5.5	2.3	114
50-250C	7.1 10.0 13.1	1.97 2.78 3.64	53.2 52 50.4	36	2900	5.5	2.3	108
50-100(I)	17.5	4.86	13.7	67	2900	1.5	2.5	41

联系电话: 021-60641032,

企业网址: www.pumpbq.com

	25 32.5	6.94 9.03	12.5 10.5	69 69				
50-100(I)A	15.6 22.3 29	4.3 6.19 8.1	11 10 8.4	65 67 68	2900	1.1	2.5	36
50-125(I)	17.5 25 32.5	4.86 6.94 9.03	21.5 20 18	60 68 67	2900	3.0	2.5	56
50-125(I)A	15.6 22.3 29	4.33 6.19 8.1	17 16 13.6	58 66 65	2900	2.2	2.5	48

从 50-160(I) 至 80-125A, 流量: 15m³/h—58m³/h

型 号	流量		扬程 (m)	效率 (%)	转速 (r/min)	电机功率 (kw)	汽蚀余量 (NPSH)r	重量 (kg)
	m ³ /h	L/s						
50-160(I)	17.5	4.68	34.4	54	2900	4.0	2.5	72
	25	6.94	32	63				
	32.5	9.03	27.5	60				
50-160(I)A	16.4	4.56	30	54	2900	3.0	2.5	71
	23.4	6.5	28	62				
	30.4	8.44	24	59				
50-160(I)B	15.0	4.17	26		2900	2.2	2.5	59
	21.6	6.0	24	58				
	28	7.78	20.6					
50-200(I)	17.5	4.86	52.7	49	2900	7.5	2.5	108
	25	6.94	50	58				
	32.5	9.03	45.5	59				
50-200(I)A	16.4	4.56	46.4	48	2900	5.5	2.5	107
	23.5	6.53	44	57				
	30.5	8.47	40	58				
50-200(I)B	15.2	4.22	40		2900	4	2.5	100
	21.8	6.06	38	55				
	28.3	7.86	34.5					
50-250(I)	17.5	4.86	82	39	2900	15.0	2.5	175
	25	6.94	80	50				
	32.5	9.03	76.5	52				
50-250(I)A	16.4	4.56	71.5	39	2900	11.0	2.5	165
	23.4	6.5	70	50				
	30.5	8.47	67	52				
50-250(I)B	15	4.17	61	38	2900	7.5	2.5	165
	21.6	6.0	60	49				
	28	7.78	57.4	54				

50-315(I)	17.5 25 32.5	4.86 6.94 9.03	128 125 122	30 40 44		2900	30.0	2.5	310
50-315(I)A	16.6 23.7 31	4.61 6.58 8.6	115 113 110	30 40 44		2900	22	2.5	245
50-315(I)B	15.7 22.5 29.2	4.36 6.25 8.0	103 101 98		39	2900	18.5	2.5	215
50-315(I)C	14.4 20.6 26.8	4.0 5.72 7.44	86 85 83		38	2900	15.0	2.5	195
65-100	17.5 25 32.5	4.86 6.94 9.03	13.7 12.5 10.5	67 69 69		2900	1.5	2.5	46
65-100A	15.6 22.3 29	4.3 6.19 8.1	11 10 8.4	65 67 68		2900	1.1	2.5	41
65-125	17.5 25 32.5	4.86 6.94 9.03	21.6 20 18	60 68 67		2900	3	2.5	58
65-125A	15.6 22.3 29	4.33 6.19 8.1	17 16 14.4	58 66 65		2900	2.2	2.5	49
65-160	17.5 25 32.5	4.86 6.94 9.03	34.4 32 27.5	54 63 60		2900	4.0	2.5	75
65-160A	16.4 23.4 30.4	4.56 6.5 8.44	30 28 24	54 62 59		2900	3	2.5	75
65-160B	15.0 21.6 28	4.17 6.0 7.78	26 24 20.6		58	2900	2.2	2.5	63
65-200	17.5 25 32.5	4.86 6.94 9.03	52.7 50 45.5	49 58 59		2900	7.5	2.5	107
65-200A	16.4 23.5 30.5	4.56 6.53 8.47	46.4 44 40	48 57 58		2900	5.5	2.5	107
65-200B	15.2 21.8 28.3	4.22 6.06 7.86	40 38 34.5		55	2900	4	2.5	100

65-250	17.5	4.86	82	39	2900	15	2.5	180
	25	6.94	80	50				
	32.5	9.03	76.5	52				
65-250A	16.4	4.56	71.5	39	2900	11	2.5	170
	23.4	6.5	70	50				
	30.5	8.47	67	52				
65-250B	15	4.17	61	38	2900	7.5	2.5	170
	21.6	6.0	60	49				
	28	7.78	57.4	54				
65-315	17.5	4.86	127	32	2900	30	2.5	320
	25	6.94	125	40				
	32.5	9.03	122	44				
65-315A	16.6	4.61	115	32	2900	22	2.5	255
	23.7	6.58	113	40				
	31	8.6	110	44				
65-315B	15.7	4.36	103		2900	18.5	2.5	225
	22.5	6.25	101	39				
	29.2	8.0	98					
65-315C	14.4	4.0	86		2900	15	2.5	205
	20.6	5.72	85	38				
	26.8	7.44	83					
65-100(I)	35	9.72	13.8	67	2900	3	3.0	63
	50	13.9	12.5	73				
	65	18.1	10	70				
65-100(I)A	31.3	8.7	11	66	2900	2.2	3.0	53
	44.7	12.4	10	72				
	58	16.1	8	69				
65-125(I)	35	9.72	22	67	2900	5.5	3.0	99
	50	13.9	20	72.5				
	65	18.1	17	70				
65-125(I)A	31.3	8.7	17.5	66	2900	4	3.0	78
	45	12.5	16	71				
	58	16.1	13.6	69				
65-160(I)	35	9.72	35	63	2900	7.5	3.0	103
	50	13.9	32	71				
	65	18.1	28	70				
65-160(I)A	32.7	9.1	30.6	62	2900	5.5	3.0	103
	46.7	13	28	70				
	61	16.9	24	69				
65-160(I)B	30.3	8.4	26		2900	4	3.0	97
	43.3	12.0	24	69				
	56.3	15.6	21					

65-200(I)	35	9.72	53.5	55	2900	15	3.0	176
	50	13.9	50	67				
	65	18.1	46	68				
65-200(I)A	32.8	9.1	47	54	2900	11	3.0	166
	47	13.1	44	66				
	61	16.9	40	67				
65-200(I)B	30.5	8.5	40.6		2900	7.5	3.0	114
	43.5	12.1	38	65				
	56.6	15.7	33.4					
65-250(I)	35	9.72	83	52	2900	22	3.0	235
	50	13.9	80	59				
	65	18.1	72	60				
65-250(I)A	32.5	9.0	73	52	2900	18.5	3.0	205
	46.7	13.0	70	59				
	61	16.9	63	60				
65-250(I)B	30	8.3	62		2900	15	3.0	180
	43.3	12	60	58				
	56	15.6	54					
65-315(I)	35	9.72	128	44	2900	37	3.0	350
	50	13.9	125	54				
	65	18.1	121	57				
65-315(I)A	32.5	9.0	112.6	43	2900	30	3.0	335
	46.5	12.9	110	54				
	60.5	16.8	106.4	57				
65-315(I)B	31	8.6	102.5		2900	30	3.0	335
	44.5	12.4	100	53				
	58	16.1	98					
65-315(I)C	29	8.1	87		2900	22	3.0	270
	41	11.4	85	51				
	53.6	14.9	83					
80-100	35	9.72	13.8	67	2900	3	3.0	63
	50	13.9	12.5	73				
	65	18.1	10	70				
80-100A	31.3	8.7	11	66	2900	2.2	3.0	54
	44.7	12.5	10	72				
	58	16.1	8	69				
80-125	35	9.72	22	67	2900	5.5	3.0	99
	50	13.9	20	72.5				
	65	18.1	17	70				
80-125A	31.3	8.7	17.5	66	2900	4	3.0	79
	45	12.5	16	71				
	58	16.1	13.6	69				

从 80-160 至 100-350, 流量: 35m³/h—192m³/h

型 号	流量		扬程 (m)	效率 (%)	转速 (r/min)	电机功率 (kw)	汽蚀余量 (NPSH)r	重量 (kg)
	m ³ /h	L/s						
80-160	35	9.72	35	63	2900	7.5	3.0	105
	50	13.9	32	71				
	65	18.1	28	70				
80-160A	32.7	9.1	30.6	62	2900	5.5	3.0	105
	46.7	13.0	28	70				
	61	16.9	24	69				
80-160B	30.3	8.4	26		2900	4	3.0	98
	43.3	12.0	24	69				
	56.3	15.6	21					
80-200	35	9.72	53.5	55	2900	15	3.0	175
	50	13.9	50	67				
	65	18.1	46	68				
80-200A	32.8	9.1	47	54	2900	11	3.0	165
	47	13.1	44	66				
	61	16.9	40	67				
80-200B	30.5	8.5	40.6		2900	7.5	3.0	115
	43.5	12.1	38	65				
	56.6	15.7	33.4					
80-250	35	9.72	83	52	2900	22	3.0	240
	50	13.9	80	59				
	65	18.1	72	60				
80-250A	32.5	9.0	73	52	2900	18.5	3.0	210
	46.7	13.0	70	59				
	61	16.9	63	60				
80-250B	30	8.3	62		2900	15	3.0	185
	43.3	12.0	60	58				
	56	15.6	54					
80-315	35	9.72	128	43	2900	37	3.0	355
	50	13.9	125	54				
	65	18.1	122	57				
80-315A	32.5	9.0	112.6	43	2900	30	3.0	340
	46.5	12.9	110	54				
	60.5	16.8	107.4	57				
80-315B	31	8.6	102.5		2900	30	3.0	340
	44.5	12.4	100	53				
	58	16.1	98					
80-315C	29	8.1	98		2900	22	3.0	275
	41	11.4	85	51				
	53.6	14.9	83					

80-350	35 50 65	9.72 13.9 18.1	146 150 142	55 66 67	2900	55	3.0	570
80-350A	31 44.5 58	8.6 12.4 16.1	138.4 142 134.8		2900	45	3.0	470
80-350B	29 41 53.6	8.1 11.4 14.9	131.4 135 127.8		2900	37	3.0	440
80-100(I)	70 100 130	19.4 27.8 36.1	13.6 12.5 11	66 76 75	2900	5.5	4.5	108
80-100(I)A	62.6 89 116	17.4 24.7 32.2	11 10 8.8	64 74 74	2900	4	4.5	87
80-125(I)	70 100 130	19.4 27.8 36.1	23.5 20 14	70 76 65	2900	11	4.5	163
80-125(I)A	62.6 89 116	17.4 24.7 32.2	19 16 11	68 74 65	2900	7.5	4.5	113
80-160(I)	70 100 130	19.4 27.8 36.1	36.5 32 24	70 76 65	2900	15	4.5	184
80-160(I)A	65.4 93.5 121.6	18.2 26.0 33.8	32 28 21	68 74 67	2900	11	4.5	174
80-160(I)B	60.6 86.6 112.5	16.8 24.1 31.3	72 24 18		2900	7.5	4.5	174
80-200(I)	70 100 130	19.4 27.8 36.1	54 50 42	65 74 73	2900	22	4.0	251
80-200(I)A	65.4 93.5 121.6	18.2 26.0 33.8	47.5 44 37	67 73 72	2900	18.5	4.0	220
80-200(I)B	61 87 113	16.9 24.2 31.4	41 38 32		2900	15	4.0	198
80-250(I)	70 100 130	19.4 27.8 36.1	87 80 68	62 69 68	2900	37	4.0	330
80-250(I)A	65.4 93.5	18.2 26.0	76 70	61 68	2900	30	4.0	315

	121.6	33.8	59.5	67				
80-250(I)B	61	16.9	65					
	87	24.2	60	66	2900	22	4.0	315
	113	31.4	51					
80-315(I)	70	19.4	132	55				
	100	27.8	125	66	2900	75	4.0	675
	130	36.1	114	67				
80-315(I)A	66.5	18.5	119	55				
	95	26.4	113	66	2900	55	4.0	535
	123.6	34.3	103	67				
80-315(I)B	63	17.5	106.6					
	90	25	101	65	2900	45	4.0	420
	117	32.5	92					
80-315(I)C	58	16.1	90					
	82	22.8	85	63	2900	37	4.0	366
	107	29.7	76					
100-100	70	19.4	13.6	66				
	100	27.8	12.5	76	2900	5.5	4.5	113
	130	36.1	11	75				
100-100A	62.6	17.4	11	64				
	89	47	10	74	2900	4	4.5	91
	116	32.2	8.8	74				
100-125	70	19.4	23.5	70				
	100	27.8	20	76	2900	11	4.5	169
	130	36.1	14	65				
100-125A	62.6	17.4	19	68				
	89	24.7	16	74	2900	7.5	4.5	118
	116	32.2	11	63				
100-160	70	19.4	36.5	70				
	100	27.8	32	76	2900	15	4.5	191
	130	36.1	24	65				
100-160A	65.4	18.2	32	68				
	93.5	26.0	28	74	2900	11	4.5	181
	121.6	33.8	21	67				
100-160B	60.6	16.8	27					
	86.6	24.1	24	72	2900	7.5	4.5	181
	112.5	31.3	18					
100-200	70	19.4	54	65				
	100	27.8	50	74	2900	22	4.0	245
	130	36.1	42	73				
100-200A	65.4	18.2	47.5	64				
	93.5	26.0	44	73	2900	18.5	4.0	215
	121.6	33.8	37	72				

100-200B	61 87 113	16.9 24.2 31.4	41 38 32					
				71	2900	15	4.0	193
100-250	70 100 130	19.4 27.8 36.1	87 80 68	62 69 68				
					2900	37	4.0	345
100-250A	65.4 93.5 121.6	18.2 26.0 33.8	76 70 59.5	61 68 67				
					2900	30	4.0	330
100-250B	61 87 113	16.9 24.2 31.4	65 60 51					
				66	2900	33	4.0	330
100-315	70 100 130	19.4 27.8 36.1	132 125 114	55 66 67				
					2900	75	4.0	689
100-315A	66.5 95 123.6	18.5 26.4 34.3	119 113 103	65 66 67				
					2900	55	4.0	549
100-315B	63 90 117	17.5 25 32.5	106.6 101 92					
				65	2900	45	4.0	439
100-315C	58 82 107	16.1 22.8 29.7	90 85 76					
				63	2900	37	4.0	385
100-100(I)	96 160 192	26.7 44.4 53.3	14 12.5 10	64 73 70				
					2900	11	4.5	115
100-125(I)	96 160 192	26.7 44.4 53.3	24 20 14	62 74 69				
					2900	15	4.5	168
100-125(I)A	84 140 168	23.3 39 46.7	20 17 12	64 72 68				
					2900	11	4.5	168
100-160(I)	96 160 192	26.7 44.4 53.3	36 32 27	69 79 75				
					2900	22	5.6	210
100-160(I)A	84 140 168	23.3 39 46.7	32 28 23.5	66 76 72				
					2900	18.5	5.0	210
100-200(I)	96 160 192	26.7 44.4 53.3	53 50 45	69 79 78				
					2900	37	5.2	402
100-200(I)A	84 140	23.3 39	48 45	64 74				
					2900	30	4.5	395

联系电话: 021-60641032,

企业网址: www.pumpbq.com

	168	46.7	40	73				
100-200(I)B	60	16.7	43					
	100	27.8	40	72	2900	22	4.5	360
	120	33.3	36					
100-250(I)	96	26.7	83	65				
	160	44.4	80	77	2900	55	4.8	560
	192	53.3	72	74				
100-250(I)A	84	23.3	75	60				
	140	39	72	72	2900	45	4.5	420
	168	46.7	65	69				
100-250(I)B	60	16.7	68					
	100	27.8	65	70	2900	37	4.5	400
	120	33.3	58					
100-350	60	16.7	153.6	72				
	100	27.8	150	57	2900	90	4.0	950
	120	33.3	142	74				
100-350A	61	16.9	145.6					
	87	24.2	142	75	2900	75	4.0	830
	113	31.4	134					

从 100-350B 至 200-315 (I), 流量: 58m³/h—520m³/h

型号	流量		扬程 (m)	效率 (%)	转速 (r/min)	电机功率 (kw)	汽蚀余量 (NPSH)r	重量 (kg)
	m ³ /h	L/s						
100-350B	58	16.1	138.6					
	82	22.8	135	75	2900	55	4.0	600
	107	29.7	127					
125-100	96	26.7	13					
	160	44.4	12.5	82	2900	11	4.0	180
	192	53.3	12					
125-100A	86	23.9	10.4					
	143	39.7	10	77	2900	7.5	4.0	125
	172	47.8	9.6					
125-125	96	26.7	22.6					
	160	44.4	20	80	2900	15	4.0	220
	192	53.3	17					
125-125A	86	23.9	18					
	143	39.7	16	77	2900	11	4.0	210
	172	47.8	13.6					
125-160	96	26.7	36					
	160	44.4	32	78	2900	22	4.0	265
	192	53.3	28					
125-160A	90	25	31.5					
	150	41.7	28	76	2900	18.5	4.0	230

	180	50	24.5					
125-160B	83	21.7	27					
	138	38.3	24	73	2900	15	4.0	215
	166	46.1	21					
125-200	96	26.7	55					
	160	44.4	50	77	2900	37	5.5	395
	192	53.3	46					
125-200A	90	25	48.4					
	150	41.7	44	76	2900	30	5.5	380
	180	50	40.5					
125-200B	83	21.7	41.3					
	138	38.3	37.5	75	2900	22	5.5	320
	166	46.1	34.5					
125-250	96	26.7	87					
	160	44.4	80	75	2900	55	5.0	580
	192	53.3	73					
125-250A	90	25	76					
	150	41.7	70	74	2900	45	5.5	490
	180	50	84					
125-250B	83	21.7	65					
	138	38.3	60	73	2900	37	5.5	430
	166	46.1	55					
125-315	96	26.7	133					
	160	44.7	125	70	2900	90	5.0	790
	192	53.3	119					
125-315A	90	25	117					
	150	41.7	110	70	2900	75	5.0	710
	180	50	104.6					
125-315B	86	23.9	106.4					
	143	39.7	100	69	2900	75	5.0	705
	172	47.8	95.2					
125-315C	80.5	22.4	96					
	134	37.2	88	67	2900	55	5.0	585
	161	44.7	86					
150-125	96	26.7	22.6	66				
	160	44.4	24	76	2900	11	4.0	210
	192	53.3	17	76				
150-125A	90	25	18					
	150	41.7	16	77	2900	7.5	4.0	130
	180	50	13.6					
150-160	96	26.7	36					
	160	44.4	32	75	2900	22	4.0	270
	192	53.3	27					

150-160A	90 150 180	25 41.7 50	32 28 23.5					
				76	2900	18.5	4.0	230
150-160B	84 140 168	23.3 39 46.7	27 24 21					
				73	2900	15	4.0	220
150-200	140 200 260	38.9 55.6 72.2	13.8 12.5 10.6	68 78 78	1450	15	3.0	265
150-200A	125 176 232.5	34.7 49.7 64.6	11 10 8.5	66 76 76	1450	11	3.0	244
150-200B	84 140 168	23.3 39 46.7	41 38 34					
				75	2900	22	4.0	275
150-250	140 200 260	38.9 55.6 72.2	21.8 20 17	73 79 77	1450	18.5	3.0	300
150-250A	129 184.4 240	35.8 51.2 66.7	18.5 17 14.4	72 78 76	1450	15	3.0	262
150-250B	117 167 217.5	32.5 46.4 60.4	15.2 14 12					
				76	1450	11	3.0	241
150-315	140 200 260	38.9 55.6 72.2	33.8 32 28	70 78 73	1450	30	2.5	410
150-315A	131 187 243	36.4 51.9 67.5	29.5 28 24.5	69 77 77	1450	22	3.5	335
150-315B	121 173 225	33.5 48.1 62.5	25 24 21					
				76	1450	18.5	3.5	315
150-350	96 160 192	26.7 44.4 53.3	153.6 150 142.8					
				80	2900	110	5.5	970
150-350A	90 150 180	25 41.7 50	145.6 142 134.8					
				70	2900	90	5.2	790
150-350B	84 140 168	23.3 39 46.7	138.8 135 127.8	65 76 74	2900	75	5.5	705
150-400	140 200	38.9 55.6	53 50	68 75	1450	45	3.5	490

	260	72.2	44	71				
150-400A	131	36.4	46.6	67	1450	37	3.5	454
	187	51.9	44	74				
	243	67.5	38.3	70				
150-400B	122	33.9	40		1450	30	3.5	435
	174	48.3	38	73				
	226.5	62.9	33					
150-400C	112	31.1	34		1450	22	3.5	365
	160	44.4	32	71				
	208	57.8	28					
150-250(I)	120	33.3	87	65	2900	75	4.5	702
	200	55.6	80	76				
	240	66.7	72	74				
150-250(I)A	112	31.1	76	64	2900	55	4.5	561
	187	51.9	70	75				
	224	62.2	63	73				
150-250(I)B	104	28.9	65	63	2900	45	4.5	460
	173	48.1	60	74				
	208	57.8	54	72				
150-315(I)	120	33.3	133	58	2900	110	4.5	980
	200	55.6	125	73				
	240	66.7	120	75				
150-315(I)A	112	31.1	116	57	2900	90	4.5	800
	187	51.9	110	72				
	224	62.2	105	74				
150-315(I)B	104	28.9	100	55	2900	75	4.5	724
	173	48.1	95	70				
	208	57.8	91	72				
200-200	140	38.9	13.8	68	1450	15	3.0	265
	200	55.6	12.5	78				
	260	72.2	10.6	78				
200-200A	125	34.7	11	66	1450	11	3.0	244
	179	49.7	10	76				
	232.5	64.6	8.5	76				
200-250	140	38.9	21.8	73	1450	18.5	3.0	305
	200	55.6	20	79				
	260	72.2	17	77				
200-250A	129	35.8	18.5	72	1450	15	3.0	267
	184.4	51.2	17	78				
	240	66.7	14.4	76				
200-250B	117	32.5	15.2		1450	11	3.0	246
	167	46.4	14	76				
	217.5	60.4	12					

联系电话: 021-60641032,

企业网址: www.pumpbq.com

200-315	140	38.9	33.8	70	1450	30	3.5	417
	200	55.6	32	78				
	260	72.2	28	78				
200-315A	131	36.4	29.5	69	1450	22	3.5	342
	189	51.9	28	77				
	243	67.5	24.5	77				
200-315B	121	33.6	25		1450	18.5	3.5	322
	173	48.1	24	76				
	225	62.5	21					
200-400	140	38.9	53	68	1450	45	3.5	498
	200	55.6	50	75				
	260	72.2	44	71				
200-400A	131	36.4	46.6	67	1450	37	3.5	462
	187	51.9	44	74				
	243	67.5	38.3	70				
200-400B	122	33.9	40		1450	30	3.5	443
	174	48.5	38	73				
	226.5	62.9	33					
200-400C	112	31.3	34		1450	22	3.5	373
	160	44.4	32	71				
	208	57.8	28					
200-200(I)	280	77.8	13.4	70	1450	22	4.0	382
	400	111.1	12.5	80				
	520	144	10.5	79				
200-200(I)A	250	69.4	10.7	68	1450	18.5	4.0	346
	358	90.4	10	78				
	465	129.2	8.5	77				
200-250(I)	280	77.8	22.2	75	1450	30	4.0	475
	400	111.1	20	80				
	520	144	14	72				
200-250(I)A	250	69.4	18	73	1450	20	4.0	405
	358	99.4	14	78				
	465	129.2	11.2	70				
200-250(I)B	226	62.8	14.4	70	1450	18.5	4.0	387
	322	89.4	13	75				
	419	116.4	7.3	67				
200-315(I)	280	77.8	36	73	1450	55	4.0	675
	400	111.4	32	80				
	520	144	26	75				

从 200-315 (I) A 至 500-315, 流量: 262m³/h—1450m³/h

型 号	流量		扬程 (m)	效率 (%)	转速 (r/min)	电机功率 (kw)	汽蚀余量 (NPSH)r	重量 (kg)
	m ³ /h	L/s						

200-315(I)A	262	72.8	31.5	72				
	374	103.9	28	79	1450	45	4.0	560
	486	135	23	74				
200-315(I)B	242	67.2	27					
	346	96.1	24	78	1450	37	4.0	535
	450	125	19.5					
200-400(I)	280	77.8	54.5	75				
	400	111.4	50	81	1450	75	4.0	830
	520	144	39	77				
200-400(I)A	262	72.8	48					
	374	103.9	44	80	1450	75	4.0	830
	486	135	34					
200-400(I)B	242	67.2	41.4					
	346	96.1	38	78	1450	55	5.0	685
	450	125	29.6					
200-400(I)C	224	62.2	34.9					
	320	88.9	32	76	1450	45	5.0	580
	416	115.6	25					
250-250	350	97.2	22	78				
	550	152.8	20	82	1450	45	5.0	620
	650	180.5	16	81				
250-250A	300	18.3	18.3	76				
	500	139	17	80	1450	37	5.0	550
	600	166.7	14	80				
250-235	300	83.3	14	73				
	500	139	12.5	78	1480	22	4.5	410
	600	166.7	11	70				
250-300	300	83.3	22					
	500	139	20	78	1480	37	4.5	550
	600	166.7	16					
250-315	350	97.2	34	76				
	550	152.8	32	80	1450	75	5.5	890
	650	180.5	28	79				
250-315A	300	83.3	29.5	74				
	500	139	28	78	1450	55	5.5	690
	600	166.7	24	77				
250-315B	260	72.2	25	70				
	450	125	24	74	1450	45	5.5	620
	520	144.4	20	72				
250-400	300	83.3	54.5					
	500	139	50	72	1480	90	4.5	1530
	600	166.7	39					
300-235	540	150	20.5	77				
	720	200	18	81	1450	55	5.0	1075

	900	250	15.0	74				
300-235A	450	125	17.2	74	1450	45	5.0	970
	600	166	15	79				
	720	200	12.5	77				
300-235B	420	116.7	14.3	73	1450	37	5.0	925
	540	150	12.8	78				
	650	181	10.5	70				
300-250	540	150	22.5	80	1450	55	6.0	1085
	720	200	20	83				
	900	250	17	84				
300-250A	450	136	19.5		1450	45	6.0	980
	600	166	17	81				
	720	200	14					
300-300	540	150	32		1480	75	5.0	1230
	720	200	28	82				
	900	250	23					
300-300A	450	125	27.5		1480	75	5.0	1095
	600	166	24	80				
	720	200	20					
300-300B	420	116.7	24		1480	55	5.0	980
	540	150	21	78				
	650	181	17					
300-315	540	150	35		1480	90	4.5	1350
	720	200	32	84				
	900	250	26					
300-315A	460	127.8	31.5		1480	75	4.5	1240
	650	180	28	80				
	800	222	23.5					
300-315B	420	116.7	27		1480	55	4.5	1100
	580	161	24	78				
	700	194	20.0					
300-380	480	133.3	48		970	132.0	5.0	1900
	720	200	44	84				
	900	250	34					
300-380A	444	123.3	41.4		970	110.0	5.0	1700
	666	185	38	80				
	833	231.4	30					
300-380B	400	113.6	35		970	90.0	5.0	1530
	614	170.6	32	78				
	764	213.1	35					
300-390	540	150	20.5	78	980	55	5.0	1300
	720	200	18	81				
	900	250	15.5	76				

联系电话: 021-60641032,

企业网址: www.pumpbq.com

300-390A	450	126	17.2	77	980	45	5.0	1220
	600	167	15	79				
	720	200	12.8	75				
300-390B	400	111	14	74	980	37	5.0	1100
	540	150	12.5	77				
	650	180	11.5	76				
300-400	450	125	55		1480	110	5.0	1500
	600	166	50	78				
	720	200	42.5					
300-480	540	150	31	79	980	75	5.0	1500
	720	200	28	81				
	900	250	24	80				
300-480A	450	126	27.4	78	980	75	5.0	1280
	600	166	24	80				
	720	200	20.0	79				
300-480B	400	111	24		980	55	5.0	1180
	540	150	21	79				
	650	180	17					
350-235	600	167	14	80	1480	37	4.5	1050
	800	222	12.5	83				
	960	267	10.5	82				
350-300	600	167	22.5	79	1480	55	4.5	1230
	800	222	20	82				
	960	267	17.5	71				
350-315	600	167	35.5		1480	90	4.5	1650
	800	222	32	84				
	960	267	28.5					
350-400	600	167	55		1480	160	4.5	1950
	800	222	50	83				
	960	267	45.5					
400-300	920	228	23		1480	90	6.0	1570
	1080	300	20	78				
	1300	361	16					
400-315	820	205	36.5		1480	132	6.0	1880
	1080	300	32	76				
	1300	344	27					
500-300	1000	277.8	23		1480	110	6.0	1800
	1200	333	20	80				
	1450	403	16.0					
500-315	1000	278	34.5		1480	160	6.0	2070
	1200	333	32	78				
	1450	403	27					